



CONVERTIDOR DE MEDIOS Y MÓDULO

Standards and Protocols	IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x
Basic Function	Full Duplex Flow Control (IEEE 802.3x) Extends fiber distance up to 0.5km using 50/125µm OM3
Interface	1 Gigabit SFP port 1 1000M RJ45 port (Auto MDI/MDIX)
Wave Length	Depends on the used SFP module
Network Media 1000BASE-FX	Multi-mode/Single-mode SFP module
Network Media 1000BASE-X	Multi-mode/Single-mode SFP module
Network Media 1000BASE-T	UTP category 5, 5e, 6 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Dimensions (W x D x H)	3.7*2.9*1.1 in. (94.5*73.0*27.0 mm)
Power Supply	External Power Adapter
Max. Power Consumption	1.7W
LED	PWR, LINK, RX
Safety & Emission	FCC, CE
Package Content	<ul style="list-style-type: none">• Media Converter MC220L• Power Adapter• Installation Guide



CONVERTIDOR DE MEDIOS Y MÓDULO

Environment	Operating Temperature: 0~40 (32~104) Storage Temperature: -40~70 (-40~158) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
-------------	--